PERMANENT PAVEMENT MARKING PLAN NOTES & GUIDELINES

NOTES & GUIDELINES

GENERAL INFORMATION:

- 1. SEE 2582 IN THE SPECIAL PROVISIONS FOR PAVEMENT MARKING SPOTTING RESPONSIBILITIES.
- 2. EDGE LINES AND LANE LINES ARE TO BE BROKEN ONLY AT INTERSECTIONS WITH PUBLIC ROADS, AND AT PRIVATE ENTRANCES IF THEY ARE CONTROLLED BY AN AGENCY PLACED YIELD SIGN, STOP SIGN OR TRAFFIC SIGNAL. THE BREAK POINT IS TO BE AT THE START OF THE MAINLINE RADIUS.
- 3. DO NOT APPLY THE PAVEMENT MARKINGS WHEN WEATHER AND OTHER CONDITIONS CAUSE A FILM OF DUST OR DEBRIS TO BE DEPOSITED ON THE PAVEMENT SURFACE AFTER CLEANING AND BEFORE THE MARKING MATERIAL IS APPLIED.
- 4. THE FILLING OF TANKS, POURING OF MATERIALS OR CLEANING OF EQUIPMENT SHALL NOT BE PERFORMED ON UNPROTECTED PAVEMENT SURFACES UNLESS ADEQUATE PROVISIONS ARE MADE TO PREVENT SPILLAGE OF MATERIAL.

CONTRAST MARKINGS

1. CONTRAST MARKINGS ARE DEFINED AS STANDARD LINEAR PAVEMENT MARKINGS, CROSSWALK MARKINGS AND PAVEMENT MESSAGES WITH 1.5 INCH NON REFLECTIVE BLACK BORDERS.

\int		\checkmark
\geq	DESIGNER'S NOTES:	\prec
\geq	REMOVE ALL UNNECESSARY MATERIAL NOTES FROM TITLE SHEET.	\prec
\succ		\prec
\geq	THIS SPACE MAY BE USED FOR PERMANENT PAVEMENT MARKING TABULATIONS.	\prec
L		كر

y an agency i surface after Dequate	PERMANENT PAVEMENT MARKING PLAN INDEX o permanent pavement marking title sheet o permanent pavement marking tabulations o interim pavement markings o-o details o-o typicals		
	SYMBOLS & MATERIALS LEGEND		
TIVE BLACK BORDERS.	BROKEN LINE-50' CYCLE (10' LINE, 40' GAP)		
	DOTTED LINE-15' CYCLE (3' LINE, 12' GAP), UNLESS SHOWN OTHER WISE IN THE PLAN		
	CROSSWALK BLOCK		
	PAVEMENT MESSAGE (LEFT ARROW)		
	STRIPING KEY		
	CIRCLE-MULTI COMP BOX-PREF TAPE		
	TRIANGLE-PAINT OCTAGON-PREF THERMO		
	1ST DIGIT 2ND DIGIT 3RD DIGIT WIDTH PATTERN COLOR 4", 8", ETC. S - SOLID W - WHITE B - BROKEN Y - YELLOW D - DOUBLE SOLID B - BLACK K - DOUBLE BROKEN H - DOUBLE DOTTED		
	G=GROUND IN W=WET REFLECTIVE C=CONTRAST E=ENHANCED SKID RESISTANCE EXAMPLE: 4SW GCW = 4" SOLID LINE WHITE PREF THERMO GROUND IN, CONTRAST, WET REFLECTIVE		
	I HEREBY CERTIFY THAT SHEETS 000 THROUGH 000 OF THIS PLAN WERE PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MINNESOTA. PRINT NAME: ENGR NAME HERE DATE: \$IDATE!\$ SIGNATURE: DESIGNER TECH NAME HERE		
	PERMANENT PAVEMENT MARKING TITLE SHEET		
STATE PROJ. NO. 0000-000 (TH 000) SHEET NO. PMXXX OF PMXXX SHEETS			